N\A	Intermodulation 3rd order
≥0.28N	Center conductor retention force
≪2.5mΩ	Conductor contact resistance
≪3mΩ	Center pin contact resistance
≥5000MΩ	Insulation resistance
1000 V rms	Test voltage
335 V rms	working voltage
$\leq 0.1 \text{ x } \sqrt{f(GHz)} \text{ dB}$	withstand voltage
≤1. 15 (DC~8GHz)	Standing wave ratio(VSWR)
DC to 8 GHz	Frequency range
50 Ω	Characteristic impedance
	Electrical performance

2008. 12. 27 Date

Owner ZXM

≥500 cycles	durability
N\A	Airtight
48H	Salt spray test time
−40~+155°C	Tempreture range
onment	Mechanical and environment

Materials		
Connector parts	Material	Plating
Center contact	brass	Au
Outer contact	brass	Au
Dielectric	PTFE	

DO NOT MANITALLY LIDDATE	CAD GENERATED DRAWING,		Dielectric	Outer contact	Center contact	Connector parts	Materials
ALI V LIDDATE	ED DRAWING,		PTFE	brass	brass	Material	
	STANDARD TO			Au	Au	Plating	

12. 2±0. 05	- 00
57	
ø 16	
1\4-36UNS-2A	,
c c	ת ת 11.
	၂ ၂
	\
	<u>.</u>
$\phi 1 27 \pm 002$	